





IEC 60269-4

Price List 2024

SEMICONDUCTOR PROTECTION gR

P.20240425

Size	Rated	Rated	Part No.	TYPE	Price	
	Current (A)	Voltage				
	NH00	35A	690V	004721209	M00CUQ2/35A/690V NH Fuse-Links size 00C for Semiconductor protection	3,000
	NH00	63A	690V	004721212	M00CUQ2/63A/690V NH Fuse-Links size 00C for Semiconductor protection	3,000
	NH00	100A	690V	004721214	M00CUQ2/100A/690V NH Fuse-Links size 00C for Semiconductor protection	3,000
	NH00	125A	690V	004721215	M00CUQ2/100A/690V NH Fuse-Links size 00C for Semiconductor protection	3,000
	NH00	160A	690V	004721216	M00CUQ2/160A/690V NH Fuse-Links size 00C for Semiconductor protection	3,000
		NH1	200A	690V	004723217	M1UQ2/200A/690V NH Fuse-Links size 1 for Semiconductor protection
NH1		250A	690V	4723219	M1UQ2/250A/690V NH Fuse-Links size 1 for Semiconductor protection	11,000



IEC 60269-1, IEC 60269-2

Price List 2024

FUSE LINK gG

P.20240425

Size	Rated	Rated	Part No.	TYPE	Price	
	Current (A)	Voltage				
	NH00	125A	690V	004182315	HRC fuse link gG 00/125A / 690V	1,600
	NH00	125A	690V	4111615	HRC fuse link gG 00/125A, 690V	1,600
	NH00	160A	690V	4111616	HRC fuse link gG 00/160 A, 690V	1,600
	NH1	250A	690V	4173115	HRC fuse link gG 1/250 A, 690V	1,700
  	D01	2A	400V	2211001	Fuse link D01 gG, E14, 2 A, 400 V	155
	D01	4A	400V	2211002	Fuse link D01 gG, E14, 4 A, 400 V	155
	D01	6A	400V	2211003	Fuse link D01 gG, E14, 6 A, 400 V	155
	D01	10A	400V	2211004	Fuse link D01 gG, E14, 10 A, 400 V	155
	D01	16A	400V	2211005	Fuse link D01 gG, E14, 16 A, 400 V	155
	D01	13A	400V	2211006	Fuse link D01 gG, E14, 13 A, 400 V	155
	D02	20A	400V	2212001	Fuse link D02 gG, E18, 20 A, 400 V	175
	D02	25A	400V	2212002	Fuse link D02 gG, E18, 25 A, 400 V	175
	D02	35A	400V	2212003	Fuse link D02 gG, E18, 35 A, 400 V	200
	D02	50A	400V	2212004	Fuse link D02 gG, E18, 50 A, 400 V	200
	D02	63A	400V	2212005	Fuse link D02 gG, E18, 63 A, 400 V	200
	D02	32A	400V	2212006	Fuse link D02 gG, E18, 32 A, 400 V	200
	D02	40A	400V	2212007	Fuse link D02 gG, E18, 40 A, 400 V	200



MICRO-SWITCH

Size	Rated	Rated	Part No.	TYPE	Price
	Current (A)	Voltage			
00-3	5A	250V	004117001	Micro Swich NVS5 (1 NC)ติดตั้งบนฟิวส์ไบเมียด Size 00-3เพื่อส่งสัญญาณ ว่าฟิวส์ขาด และตัดวงจร ทั้ง 3 เฟส	1,800

